

.375CT SUPERSPORT

EXTREME LONG RANGE (XLR) PRECISION RIFLE SYSTEM



THE .375CT SUPERSPORT XLR is engineered and designed to provide shooters with a precision rifle platform chambered in .375CT capable of precision target engagement out to 2000 yards and beyond. This precision rifle is proudly manufactured in the USA and built on the new SABER VX bolt action receiver, and the patented SABER®-FORSST® MOD-1 SuperSport modular rifle chassis system (MRCS). The ergonomically adjustable .375CT SuperSport uses a 4.40" ID 7rd detachable box magazine for long loaded match grade jacketed and monolithic solid projectiles. This hand crafted extreme long range rifle delivers consistent ½ MOA accuracy with match grade ammunition.

The .375CT SuperSport uses a 28" 1-in-10.5" twist Pinnacle Series 416 stainless steel fluted barrel, safety and performance engineered using APO's proprietary B.A.S.E.D.™ barrel engineering software. The .375CT SuperSport Pinnacle Series barrel is finished with an 11 degree target crown and highly effective new Arlight muzzle brake, substantially reducing felt recoil from this powerful super magnum cartridge. The SuperSport uses a premium tactical two-stage trigger set to 3.5 lbs. for a smooth take up and crisp let off for precision shot placement and an innovative inside-the-trigger guard safety.

The .375CT SuperSport XLR features a patented continuous full length MIL-STD 1913 40MOA monolithic 12 o'clock scope rail design that increases structural rigidity and accommodates a variety of modern "clip-on" thermal imaging and night vision devices. The Quattro Alloy Series SuperSport forend features a heat venting design with repositionable 12" and 4" accessory rail locations on the ergonomically shaped forend at 3, 6 and 9 o'clock positions.

The ergonomically adjustable folding SABER® PBA-H2 (Push Button Adjustable Hybrid2) shoulder stock is fit to the user with adjustments for length of pull, cheek-piece height, and vertical recoil pad drop that require no tools! The MRCS is also adjustable for grip-to-trigger distance and comes with a Butt Hook as standard equipment and optional adjustable field Monopod as a user installable option.



Ashbury Precision Ordnance Mfg.
A Division of Ashbury International Group, Inc.
PO Box 8024, Charlottesville, VA. 22906-8024
Tel 434-296-8600, Fax 434-296-9260
info@AshburyPrecisionOrdnance.com



AshburyPrecisionOrdnance.com

.375CT SUPERSPORT

EXTREME LONG RANGE (XLR) PRECISION RIFLE SYSTEM



Specifications

Caliber

- .375CT (optional .223, 6.5CM, .308Win, .300WM, .338LM)

Action

- SABER VX

Chassis

- SABER AVX-A1 with 8 Flushcups

Shoulder Stock

- Folding PBA-H2 with Tool-Less Ergonomic Adjustments

Barrel

- 28" Pinnacle™ Series 416R SS 5R barrels

Muzzle Brake

- Arclight

Trigger

- Huber Tactical Two Stage trigger set to approx. 3.5 lbs.

Forend

- Quattro Alloy Series SuperSport Forend with Repositionable Accessory Rail Mounting Locations at 3, 6 & 9 o'clock

Scope Rail

- 40 MOA MIL-STD 1913

Accessory Rail

- 12" Picatinny Rail w/ Flushcups x1
- 12" Picatinny Rail x2

Magazines

- A1 (7rd) detachable box magazine (one supplied)

Hand Grip

- Ergo Slimline

Grip Angle Adaptors

- 11° Standard (17.5° and 27° optional)

Surface Coatings

- Cerakote Ceramic Coating

Color

- Black (optional Flat Dark Earth, Nordic Gray, OD Green & Tungsten)

Accuracy

- ½ MOA accuracy with match grade ammunition

Weight

- 18 lbs.

Accessories:

- Leupold Mark 8 3.5 - 25 x 56mm Premium Day Optical Sight
- SABER EO Scope Rings
- 4" and 12" Side Accessory Rails
- Monopod
- Long Range Accuracy Bipods
- APO Hard Transit Case with Custom Foam
- Complete Tactical Rifle Packages



Ashbury Precision Ordnance Mfg.

A Division of Ashbury International Group, Inc.

PO Box 8024, Charlottesville, VA. 22906-8024

Tel 434-296-8600, Fax 434-296-9260

info@AshburyPrecisionOrdnance.com



AshburyPrecisionOrdnance.com